

用犀利砂带 磨世界不平

Using sharpness abrasive belt
Grinding the unsmoothness of the world



湖北玉立砂带集团股份有限公司

地址：湖北省麻城市大港218号 邮编：432400

电话：+86(0)713-4324488 4322107

传真：+86(0)713-4322111 4322118

网站：<http://www.sharpness.com.cn>

<https://sharpness.en.alibaba.com/>

电子邮箱：info@sharpness.com.cn

HUBEI YULI ABRASIVE BELTS GROUP CO., LTD.

401 No.218, Yuli Avenue, Tongcheng County, Hubei, China 432400

Tel: +86(0)713-4324488 4322107

Fax: +86(0)713-4322111 4322118

Homepage: <http://www.sharpness.com.cn>



中国驰名商标

SHARPNESS

湖北玉立砂带集团股份有限公司 2017

涂附磨具系列产品

coated abrasives



GENERAL PROFILE OF YULI

●● 玉立集团简介

湖北玉立铝业有限公司目前亚洲生产规模最大、产品产量最多、产品品种最全的铝材制造商之一公司。它是集科研、生产、经营和营销于一体的铝产业综合企业。公司拥有从国内市场占有率达70%以上，注册的“福利”牌商标为“中国的铝商标”。企业发展三十多年来，曾多次获中华人民共和国政府、国家进出口局、国家工商局、中国工业部、中国轻工业局工业部等颁发的国家荣誉证书。生产的铝棒、铝锭、铝管以及各种铝的器具、铝材器具、铝模壳壳等。铝模壳等系列产品远销世界五大洲的40多个国家和地区，并通过了欧盟的CE认证，并被国家质检总局评定为“中国出口免检企业”。

公司拥有人型铝主理人原享受国家特殊津贴专家、全国五一劳动奖章获得者、全国优秀企业家、全国40位优秀发明家之一，在行业内被中国铝业协会授予“功勋铝模壳发明家”。

Hubei Yuli Aluminum Bathy Group is the largest professional aluminum manufacturer in Asia with a full range of coated aluminum products. It is even an enterprise with long chain production capabilities integrating with scientific research, production, marketing and raw materials processing. The share of leading products in domestic market is over 70% and its brand, "YULI" is entitled as China Famous Trademark. With the national honors awarded by the State Council, the National Quality Monitoring Bureau, IACC, National Federation of Private Enterprises and CETMA in the recent developed objects. The YULI BQ constituted cutting discs and grinding wheels, aluminum chisels/pipes in self-developed, film discs, flap discs, lathe discs, sanding wheels, sanding spindles, roll wheel abrasives in self-developed, and roller printing wheels are exported to over 50 countries, and "YULI" branded products was evaluated as China's export inspection exemption products by the National Quality Monitoring Bureau. Chairman Wu (Y) Wang, as the leader of Hubei Yuli Aluminum Bathy Group, is an expert who enjoys special government allowances of the State Council, the winner of National Labor Model, the National outstanding entrepreneur and one of the 40 typical characters for the National poverty alleviation and development, especially he awarded with Top Honor Prize in coated abrasives by the CCMA.

以誠待天下 以信立門戶

Treat the world sincerely and start career with faith



PRODUCTS

产品目录

Rigid abrasive belts	硬质磨砂带系列	01
Flexible abrasive belts	软质磨砂带系列	08
Paper abrasive rolls	纸基砂带系列	15
Aluminum in sheet	铝板产品系列	21
Plasticizer film and sanding screen	塑料及网筛产品	27
Conversion abrasives	异型产品系列	29



TAX51

金属专用焊丝
Metal welding wire for metal

适用范围：适用于手工电弧焊、埋弧焊、电渣焊、气电焊、自动熔焊和脉冲焊、适用于工业用半自动电弧焊设备材料。适用于碳钢和低合金钢工业用焊丝的熔敷金属成分。

For open backing, pipe, offshore and joint heat treatments, and shipping and fast acceptance, especially steel for welding and grinding on both of metals and metal joints and metal welding.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

BKY71

氧化亚铜焊丝
Bismuth Oxide rod welding wire

适用范围：具有优良的导电性和机械性能，适用于工业用半自动电弧焊设备材料。

For copper oxide welding, high strength and mechanical grinding efficiency. Generally used for making balls for paint roller and industrial parts.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

GXK51-P

氧化亚铜焊丝
Bismuth Oxide multi-function welding wire

适用范围：适用于手工电弧焊、埋弧焊、电渣焊、气电焊、自动熔焊和脉冲焊。

For shielded metal arc welding. Generally used for furnace metal parts, mechanical industry.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

GXK51-Fe

氧化亚铜焊丝
Bismuth Oxide welding wire

适用范围：用于一般金属及合金钢的熔敷加工和加工。

For shielded metal welding. Generally used for metal and mechanical welding.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

KX167

氧化亚铜焊丝
Bismuth Oxide welding wire

适用范围：适用于手工电弧焊、埋弧焊、电渣焊、气电焊、自动熔焊和脉冲焊。

For shielded metal arc welding. Generally used for furnace metal parts, mechanical industry.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

GXK51-LD

氧化亚铜焊丝
Bismuth Oxide welding wire

适用范围：适用于手工电弧焊、用于一般金属及合金钢的熔敷加工和加工。

For shielded metal arc welding, suitable for making metal balls. Generally used for metal and mechanical welding.



成分 Composition			力学性能 Mechanical Property				使用温度 Use Temp
碳 C	锰+镍 Mn+Ni	磷+硫 P+S	抗拉 Rm	屈服 ReL	伸长 A5	冲击 KV2	
≤0.05	≤1.00	≤0.01	■	■	■	■	

CONVERSION ABRASIVES

● 异型产品系列

高档铜纸砂盘

Superior flap disc

适用范围：主要用于安装在电动或气动角磨机上的金属和特种合金金属材料的高速进行打磨、去毛刺、去漆、打磨焊缝，也是机械修理工作中磨削、磨平、磨光、磨圆的理想工具。同时该厂还用于家具行业的抛光打磨和抛光。

Superior advanced flap paper backing, inherently equipped into grinding to polish on metal and nonmetal for rust removing, deburring, scratch removing, welding joint grinding, and normally used for grinding on furniture edges and sanding.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

普通铜纸砂盘

Normal flap disc

适用范围：主要用于安装在电动或气动角磨机上的金属和特种合金金属材料的高速进行打磨、去毛刺、去漆、打磨焊缝，也是机械修理工作中磨削、磨平、磨光、磨圆的理想工具。同时该厂还用于家具行业的抛光打磨和抛光。

Normal advanced flap paper backing, inherently equipped into grinding to polish on metal and nonmetal for rust removing, deburring, scratch removing, welding joint grinding, and normally used for grinding on furniture edges and sanding.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

精密玉铜纸砂盘

Discum flap disc

适用范围：主要用于安装在电动或气动角磨机上的特种合金和合金金属材料的高速进行打磨、去毛刺、去漆、打磨焊缝，也是机械修理工作中磨削、磨平、磨光、磨圆的理想工具。同时该厂还用于家具行业的抛光打磨和抛光。

Superior advanced flap paper backing, inherently equipped into grinding to polish on metal and nonmetal for rust removing, deburring, scratch removing, welding joint grinding, and normally used for



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

泡沫磨块

foaming sponge

适用范围：使用方便，使用寿命长，具有较好的弹性和一定的韧性，不会损坏工件，并可加速工件的补料和抛光。该厂适用于各种不同形状及复杂工件的修磨。

Make of sponge foam, easy convenient and economic, soft and flexible, can be used to polish on all complex surface and corners.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

不干胶砂盘

Adhesive sanding disc

适用范围：适用于电动、气动工具对金属材料、漆层、汽车、电子等行业进行磨削抛光。

Adhesive by adhesive paper, easy to be attached into power tools to polish on metal, furniture, automobile and electronics.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

平面砂布轮

Flap disc

适用范围：广泛用于各种材料、汽车制造、造船、铁路、交通、医疗器械的抛光、修整和抛光及各种焊缝的打磨抛光。效率高，同步性强性好，使用寿命长，不损伤工件。

Optimal advanced A6, A6, A6. Generally used for rust removing, repairing and polishing on many industries such as, iron products, automobile, metal working equipments, medical instruments etc. High efficiency and fast elongation, good conformity of working and no harm to the work piece.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

干页轮

Dry wheel

弹性好，磨削量大，高速，效率高，适用范围广，主要用于金属、合金类表面处理抛光。对复杂形状进行修磨抛光，效率高，使用寿命长。

Good resilience and sanding efficiency, high speed polishing, long lasting usage. Generally used for rust removing, deburring and welding joint grinding on metal and nonmetal.



规格 Specification			尺寸 Size				重量范围 Weight range
直径 Diameter	厚度 Thickness	磨粒粒度 Grain size	直径 Diameter	厚度 Thickness	重量 Weight	重量 Weight	
磨口规格 Grind size	1/4" 6.35mm	80#					150g-170g

POLYESTER FILM AND SANDING SCREEN

●● 薄膜及网格产品

聚酯薄膜产品

Polyester film sanding roll

平抛磨砂，结构强度高，适用范围：适用于各种精密的电子元件、电器板、汽车及汽车零件、袖标、袖标内部的磨砂处理。

Polyester film sanding, good flexures and high accuracy. Generally used for sanding electronics, PCB, automotive and wheel hubs, etc. etc.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
聚酯薄膜 polyester film	1400	2000	●	●	●	P50-P1000

产品平抛磨砂，强度高，适用范围较广，中间均匀磨削，具有超值的磨削效率和磨削精度，加工精度高，表面质量佳，加工工作表面一般性好等特点。适用范围：主要适用于各种材料（如塑料、亚克力）磨削，制造各种规格的尺寸量具，用于手工或机械磨削工件平面。同时也可用于磨削抛光。

Like polyester film sanding, good flexures and high accuracy, great accuracy and precision, average sanding efficiency and excellent in grinding and wire grinding. Very good uniformity of appearance after grinding. Generally used for compound material such as springs and brass, can be converted into different shapes for manual or machine grinding on flat and complex surfaces.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
聚酯薄膜 polyester film	1400	2000	●	●	●	P50-P1000

乳皮薄膜磨砂产品

Fluorocarbon coated latex polyester film sanding roll

乳皮薄膜产品的升级产品，独特的磨砂表面，具有超值的磨削效率和磨削精度，磨削精度高，表面质量佳，不堵塞磨砂工作。适用范围：主要用于特殊磨砂产品，对金属、塑料（主要为PC电子产品外壳、摄像头镜片等）等进行表面磨削、抛光处理。

Like polyester film sanding, fluorine shape coated. The special coating greatly improved efficiency of anti-chipping and heat dissipation, especially with high accuracy and great performance. Generally convert into different shapes to polish and grind on metal, plastic, electronic parts and precision instruments.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
乳皮薄膜 fluorocarbon coated latex polyester film	1400	2000	●	●	●	P50-P1000

网格砂布

Sanding screen

适用范围：一种超值的磨削磨削工具，磨削、抛光各种金属材料磨削性好，与两个工具，可双面磨削。

Sanding screen is a new coated abrasive products with excellent performance on anti-chipping, high accuracy heat dissipation and deburring. It is suitable for workpiece and cost-effective. Generally used for grinding metal with various and grinding, can be both available. Can sanding steel during operation, no pollution.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
网格砂布 sanding screen	1400	2000	●	●	●	P50-P1000

彩色网格砂布

Coloured sanding screen

适用范围：磨削性好，打磨效率高。适用范围：广泛适用于手磨、磨削、抛光等工序，可节省十倍。适用于多种工件，磨削后无杂质可实现抛光打磨。

Sanding screen is excellent, grinding efficiency. Application: widely used for hand grinding, grinding, grinding and polishing, can save ten times. Suitable for many workpieces, grinding after no impurities can be polished.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
彩色网格砂布 coloured sanding screen	1400	2000	●	●	●	P50-P1000

植绒网格砂布

Velvet sanding screen

适用范围：磨砂性好，打磨效率高。适用范围：广泛适用于手磨、磨削、抛光等工序，可节省十倍。适用于多种工件，磨削后无杂质可实现抛光打磨。

Sanding screen is excellent, grinding efficiency. Application: widely used for hand grinding, grinding, grinding and polishing, can save ten times. Suitable for many workpieces, grinding after no impurities can be polished.



规格 specification		性能 property				耐磨范围 Abrasive range
厚度 thickness	最大宽度 max width	最大长度 max length	硬度 hardness	弹性 elasticity	伸长率 elongation	
植绒网格砂布 velvet sanding screen	1400	2000	●	●	●	P50-P1000

乳版纸涂布干砂

Latex dry sanding paper with emulsion coating

乳版纸涂布干砂，具有涂布的干砂性，适用范围：主要用于家具、木材、汽车、船体、机械钢件的打磨，固定涂层的抛光。

Report 1 Latex paper backing, emulsion coating with abrasive coating, good flexibility, generally used for polishing on furniture, metal, automobile, vessel, machine parts and precise instruments.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
乳版纸涂布干砂 Latex dry sanding paper	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

进口高韧性涂布干砂

Import latex paper sheet with abrasive coating

进口高韧性涂布干砂，具有极好的韧性，耐水、耐晒、耐各种溶剂，适用范围：主要用于家具、木材、汽车、船体、机械钢件的打磨，固定涂层的抛光。

Import Latex paper backing, extremely elastic with abrasive coating, good flexibility. Generally used for polishing on furniture, metal, automobile, vessel, machine parts and precise instruments.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
进口高韧性涂布干砂 Import latex paper sheet with abrasive coating	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

进口高韧性涂布干砂

Import latex paper sheet with abrasive coating

乳版纸、耐水耐晒、打磨快速，硬度适中，不易磨损，有耐高温型、半耐高温型、耐水、耐晒、耐溶剂，打磨工作表面光滑度好，适用范围：特别适用于油漆打磨，具有使用简单，可以磨除锈迹，可使打磨效率比打磨膏高，节能环保。

Report latex paper backing, with strong heat resistance and wear resistance, good performance, durable with special coating, easy shape grinding. Especially designed for polishing on painting and varnish, they cost effective.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
进口高韧性涂布干砂 Import latex paper sheet with abrasive coating	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

A276干砂

dry sanding paper

耐晒耐水耐晒，耐磨性高，耐各种溶剂，打磨效果好，适用范围：主要用于家具、木材、汽车、船体等钢件，漆面的打磨和抛光。

Report latex paper backing, anti-ray, heat resistant and wear resistance, good performance. Generally used for polishing on varnish and body of furniture, metal, automobile, vessel.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
A276干砂 A276 dry sanding paper	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

产品性能坚韧，强度高，耐磨性能良好，耐各种溶剂，具有超强的磨擦力和耐硬度，加工精度高，表面平整，加工工作表面一致性好等特点，适用范围：主要用于各种基材（如陶瓷、粉末等）磨光，可磨成不同规格内径磨具，用于手工或机械的各类工作平面，磨光面进行打磨和抛光。

Latex paper backing, good flexure and high intensity, good resistance, strong grinding and wear resistance, high accuracy polishing, good consistency in appearance in average size part. Generally used for peripheral materials such as ceramic and flange, can be converted into different shape for manual or machine polishing on flat and complex surfaces.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
A276干砂 A276 dry sanding paper	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

牛皮纸涂布干砂

dry sanding paper with kraft paper backing

高韧性好、耐晒、耐水耐晒，耐磨性好，适用范围：主要用于玻璃钢、漆面、漆面等打磨和抛光。

Latex paper backing, flexible and wear resistance, easy to fold, shape grinding and wear resistance. Generally used for polishing on wall, furniture and wood.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
牛皮纸涂布干砂 Kraft paper dry sanding paper	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

强度高，坚韧性好，磨削耐晒，耐各种溶剂良好，适用范围：主要用于玻璃钢、漆面等漆面打磨。

Can write paper, high intensity, flexible and strong grinding and wear resistance, generally used for polishing in automobile and furniture, marine, boring industries.

	规格 size		厚度 thickness		目数 grit				重量范围 g/㎡ (oz/yd²)
	宽度 width	长度 length	厚度 thickness	厚度 thickness	目数 grit	目数 grit	目数 grit	目数 grit	
牛皮纸涂布干砂 Kraft paper dry sanding paper	1.83m	2700x3000	0.15mm	0.15mm	80				150g-180g

石英砂木砂纸

quartz sand paper sheet

材质坚硬，采用高硬度石英砂作为磨料，它具有坚韧耐磨、切削锋利、磨料性能稳定。适用范围：打磨各种材料、腻子层，还能进行打磨抛光。

Can paper backing, quartz sand, flexible and wear resisting, sharp polishing with stable working efficiency. Generally used for polishing on all wood, putty and glass.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

玻璃砂木砂纸

glass sand paper sheet

材质坚硬，采用高硬度玻璃砂作为磨料，适用范围：它具有坚韧耐磨、切削锋利、磨料性能稳定，适用于各种材料、腻子层，还能进行打磨抛光。

Can paper backing, glass sand flexible and wear resisting, sharp polishing with stable working efficiency. Generally used for polishing on all wood, putty and glass.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

石榴石木砂纸

garnet sand paper sheet

采用高硬度石榴石作为磨料，它具有坚韧耐磨、切削锋利、磨料性能稳定。适用范围：打磨各种材料、腻子层，还能进行打磨抛光。

Can paper backing, garnet sand flexible and wear resisting, sharp polishing with stable working efficiency. Generally used for polishing on all wood, putty and glass.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

彩色木砂纸

colored sand paper sheet

适用范围：适用于各种材料、腻子层、玻璃的打磨，还可以用作涂装砂纸。

Can paper backing, colored sand. Generally used for all wood, mineral putty, glass and resin, concrete coating.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

高档木砂纸

superior sanding paper sheet

适用范围：适用于各种材料、腻子层的打磨和抛光，具有磨料持久、不脱落、强度高。

Can paper backing, aluminum oxide, generally used for polishing on wood and furniture, very good in flexible and deburring.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

磨碗纸木砂纸

heavy paper sanding sheet

适用范围：适用于各种材料、腻子层的打磨和抛光，磨碗纸木砂纸。

Can paper backing, aluminum oxide, generally used for polishing on particle board and wood floor. Can be customized.

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05	0.05	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

氧化铝木砂纸

aluminum oxide paper sheet

适用范围：适用于各种材料、腻子、玻璃的打磨和抛光。

规格 specification	厚度 thickness		尺寸 size				每卷重量 per roll weight
	厚度 thickness	厚度 thickness	长度 length	宽度 width	卷径 roll diameter	卷厚 roll thickness	
1号砂纸 1# sand paper	0.05-0.08	0.05-0.08	1.1米 1.1m	0.5米 0.5m	0.05米 0.05m	0.05米 0.05m	15kg-18kg

HEAVY ABRASIVE BELTS

●● 硬布基砂带系列

DZY71

铁轮工业磨砂带

Iron wheel abrasive belt belt

磨面粗糙，具有优良的强度和机械磨削性能，适合磨削各种铸件，用于强度不高材料，适用范围：主要用于黑色金属，有色金属，磨削非金属材料时打毛刺，光面等件，磨削度好和能防锈。

Use Notes: For abrasive belt grinding, high strength and good mechanical polishing efficiency, can be used for grinding with the heavy duty grinding on ferrous metal, non-ferrous metal and have mechanical materials, and rough grinding on materials of high strength materials.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000		■	■		1700-17100

DZY72

铁轮工业磨砂带

Iron wheel grinding belt with coarse grinding

磨面粗糙，磨削度好和防锈，强度高，机械磨削性能好，具有较好的磨削性和防锈性能，适用范围：主要用于铁合金，不锈钢，磨面粗糙，使表面形成许多粗糙金属的磨面。

Use Notes: For abrasive belt grinding with extra coarse grinding, high strength and good mechanical polishing efficiency, excellent rust resistance and anti-rusting. Typically used for stainless steel, iron, aluminum the grinding needs supercoarse belt grinding steel.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000		■	■		1700-17100

DZY76

铁轮工业磨砂带

Iron wheel grinding belt with coarse grinding

磨面粗糙，磨削度好和防锈，具有优良的强度，磨削性能，耐腐蚀性能高，加工效率高，寿命长，特别适合于合金钢磨削，可干磨和湿磨，适用范围：主要用于各种合金铸件，磨气片磨打毛，也可用于不锈钢，铁合金，磨削非金属材料时打毛。

Use Notes: For abrasive belt grinding with extra coarse grinding, high strength and good mechanical polishing efficiency, excellent rust resistance and anti-rusting. Typically used for iron or the high speed grinding on metal. Typically used for grinding metal parts, grinding surface, cast iron, stainless steel, titanium, heat resistant alloys.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000		■	■		1700-17100

GZX71

强力铁轮工业磨砂带

Superforce iron wheel for fine grinding

磨面粗糙产品中有铁轮，磨削性能好，适用范围：主要用于加工铸件，平磨削，砂带磨削产品，用于各种合金钢及磨削非金属材料时磨削和抛光。

High fine sand grinding, specially for making fine steel and fine wheels. Typically used for heat metal and nonmetal grinding.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000				■	1700-17100

磨面粗糙和磨，强度高，磨削度小，具有优良的强度和磨削性能使用寿命，适用范围：适合特殊合金或高硬度材料，对各种合金，特别是不锈钢，铁合金等工件进行强力磨削和抛光。

Coarse grinding grade, high strength, low oxidation, very high accuracy and long lasting polishing. Typically used for making into a grinding of heat of metal, especially for non-ferrous alloy materials.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000				■	1700-17100

具有强度高，磨削的磨面粗糙和特殊制造工艺生产而成，产品强度高，磨削度小，磨削效率高，具有较大的使用寿命，快速磨削和磨削磨削，效率高，磨削度好，产品强度高和寿命长，磨削度好的磨面粗糙和磨削磨削性能，可以磨削磨削材料表面快速磨削磨削，适用范围：特别适合于各种合金材料，碳钢，不锈钢材料铁轮，铁合金，铁合金，不锈钢材料，有色金属，特殊材料，平磨磨刀磨加工磨削。

High strength steel grinding, special grade and unique technology, high strength, low oxidation, high accuracy and long lasting polishing. Great heat dissipation, accurate grinding efficiency and good smoothness. The grinding surface of double grade for heat resistant materials and metal surface after polishing. Typically used for grinding titanium parts, carbon steel, iron parts, aircraft, forgings, cast parts, ferritic steel, special materials, superalloys.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000		■	■		1700-17100

磨面粗糙，具有特殊磨削和制造工艺制成，磨削性能优良，具有特殊磨削磨削性能，磨削效率高，磨削度小，适用范围：适合于各种合金及金属材料，磨削的磨面粗糙以及磨削合金钢磨削的磨削和抛光。

For steel grinding, special grade and unique technology, high performance, with special mechanical steel, strong heat dissipation, high accuracy polishing. Typically used for grinding steel and grinding all kinds of metal and metal parts and metal grinding.

规格 Size	性能 Performance			应用 Application			重量范围 Weight range
	厚度 Thickness	最大速度 Max speed	使用寿命 Service life	正压 PSI	负压 TSP	电压 V	
磨面粗糙 Roughness	1.60	8000 5000		■	■		1700-17100

PCES1-1

[illegible]

11/11/2019 10:11:11 AM
 11/11/2019 10:11:11 AM
 11/11/2019 10:11:11 AM

[illegible]

Imported and paper flooring, covered stools, (2) pendant fans, two mirrors, (2) to be made into beds and special draped products for the painting in furniture, wood floor, rubber plants, leather, wood parts, wall-to-wall.

項目	2016年度			2015年度			前年度比増減率 (%)
	数量	数量	数量	数量	数量	数量	
	数量	数量	数量	数量	数量	数量	
数量	数量	数量	数量	数量	数量	数量	数量
数量	数量	数量	数量	数量	数量	数量	数量

REPORT

	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

1. *Journal of Management Education*, 2000, 24(1), 1-10.
 2. *Journal of Management Education*, 2000, 24(1), 11-20.
 3. *Journal of Management Education*, 2000, 24(1), 21-30.

[illegible]

End organ function, especially designed to buffer very good flexibility for handling the enormous amount of energy for metabolic processes and for the many other metabolic processes.

	1990 1990年			1991 1991年			1992 1992年
	1990	1991	1992	1990	1991	1992	
	1990	1991	1992	1990	1991	1992	
1990	1991	1992					1990-1992

PK052-1

© 2004 Blackwell Publishing Ltd, *Journal of Internal Medicine* 255: 105–112

1. *Journal of Management Education*, 2000, 24(1), 1-10.
 2. *Journal of Management Education*, 2000, 24(1), 11-20.
 3. *Journal of Management Education*, 2000, 24(1), 21-30.

以上各藥均用沸水浸10分鐘，煎服6次。煎藥時，應先將藥材洗淨，並切細，然後放入鍋中，加水至藥面之上，大火煮沸後，改小火煎煮。每次煎藥時，應注意火候，以免燒焦或過火。煎藥時間應根據藥材的性質而定，一般為10-15分鐘。煎藥次數應根據病情而定，一般為每日6次。

Impact: for power loading, good shockproof and low vibration, control flexible and working force, low maintenance, and low cost and pollution, special design products. For low pollution in treatment, good effect, reduce dust, reduce noise, save material costs.

[illegible]

PCF93-1

Table 1

© 2000 Blackwell Science Ltd
Journal of Internal Medicine 247: 105–112

[illegible]

Import raw paper, including, normal finish, Re-rending raw (no extension, can be made into beds and special shaped products for the painting of furniture, wood raw, white plastic, leather, wood pulp (softwood).

	總計 (Total)			地區 (Region)				附註/備註 (Note/Remark)
	英國 (United Kingdom)	歐洲地區 (EU/EEA)	歐洲以外 (Rest of World)	英國 (UK)	歐洲 (EU)	歐洲以外 (ROW)	亞太 (APAC)	
英國 (United Kingdom)	7400		歐洲以外 (Rest of World)		■	■	■	7400 - 7400

PC052

1. The first step is to identify the problem or question that needs to be answered. This involves understanding the context and the specific requirements of the task.

© 2000 Blackwell Science Ltd
Journal of Internal Medicine 247: 105–112

附註：本表內之「不承認」，是指我國政府不承認該項組織，並非指該項組織不承認我國政府。至於「未承認」，是指我國政府與該項組織均不承認對方之地位而言。

For paper backing was missing, indicating. Generally used for affixing printing on white wood panels, especially on doors.

	原料 Raw material			燃料 Fuel			製造設備 Production equipment
	種類 Type	最大消費 最大消費量 Maximum consumption	環境影響 環境影響 Environmental impact	原料 原料 Raw material	燃料 燃料 Fuel	燃料 燃料 Fuel	
〇燃料 Fuel	4.40%	燃料 燃料 Fuel			■	■	2000-2000

PKC52

1000

Copyright © 2004 John Wiley & Sons, Ltd.
J. Polym. Sci. Part A: Polym. Chem. 42: 1005–1015 (2004)
DOI: 10.1002/pola.20000

本公司生产的塑料、橡胶、树脂材料，不挥发，使用寿命长；主要用途：主要用在汽车、游艇、船壳、汽车、塑料零件和工业用，属于塑料橡胶及加工成型塑料材料的产品和汽车零件及工业用塑料。

This paper includes, however, some minor editing, indicating, generally, and for the sake of guidance on what word, words, parts, letters and style, also can be converted into words that be attractive and useful.

項目 Item	2019 2019 (USD)		2020 2020 (USD)				投資項目 Investment
	金額 Amount	單位 Unit	投資 Invest	匯款 Remittance	轉帳 Transfer	匯款 Remittance	
(金額) (Amount)	美金 (USD)	單位 Unit	美金 (USD)	美金 (USD)	美金 (USD)	美金 (USD)	美金 (USD)

PAPER ABRASIVE ROLLS

●● 纸基砂带系列

236Ua

高韧性纸基砂带

Superior paper sanding roll with extra cutting

采用高韧性纸基砂带，适用范围：适用于各种金属表面油漆材料打磨，制造了好的打磨，特别用于家具、室内装潢、木材等行业，它独特粘性涂层设计，使产品使用寿命长于同类产品，且不含磨粒的工作，保证工作表面质量。

Superior paper sanding roll with extra cutting is available for sanding on furniture, spraying metal coating. The special anti-chipping coating improved using life and not easy to burn the work piece to ensure good performance.

规格 Size	性能 Performance			尺寸 Dimension				每卷重量 per roll (kg)
	厚度 Thickness	最大宽度 Max Width	最大长度 Max Length	宽度 Width	长度 Length	重量 Weight	长度 Length	
高韧性 Extra Cutting	1400	3000	3000	1400	3000	1400	3000	1400-3000

中韧性纸基砂带，产量较大，中等，耐磨，粘性强，适用范围：适用于各种材料打磨，特别用于汽车修理、木材打磨、家具打磨等，能减少粉尘，施工方便快捷。

该产品是工厂人的常用产品，以其卓越性能著称，满足不同需求客户要求。

Our paper has long history, reliable good service, low cost, not easy to split. Generally for automotive repair, furniture sanding, good performance after polished. It is a more economic option of 236Ua.

规格 Size	性能 Performance			尺寸 Dimension				每卷重量 per roll (kg)
	厚度 Thickness	最大宽度 Max Width	最大长度 Max Length	宽度 Width	长度 Length	重量 Weight	长度 Length	
中韧性 Medium	1400	3000	3000	1400	3000	1400	3000	1400-3000

PKE51

超耐磨纸基砂带

Superior grade that paper belt

超耐磨纸基砂带，具有适中的柔软度，砂面平整，结构细小，适合做各种砂带，砂带和砂带制品。适用范围：主要用于家具、地板、橡胶、塑料、皮革、木材、金属、人造板的打磨和抛光以及加工成各种形状的产品用于汽车等行业的工作。

For paper backing, normal flexible, the sanding belt, low abrasion, can be made into belts and special shaped products for fine sanding on furniture, wood floor, rubber, plastic, leather, metal parts, artificial board, also can be made into belts after for sanding in automotive industry.

规格 Size	性能 Performance			尺寸 Dimension				每卷重量 per roll (kg)
	厚度 Thickness	最大宽度 Max Width	最大长度 Max Length	宽度 Width	长度 Length	重量 Weight	长度 Length	
超耐磨 Superior	1400	3000	3000	1400	3000	1400	3000	1400-3000

高韧性纸基砂带砂带，具有适中的柔软度，砂面平整结构细小，适合做各种砂带，砂带和砂带制品。适用范围：主要用于家具、地板、橡胶、塑料、皮革、木材、金属、人造板的打磨和抛光以及加工成各种形状的产品用于汽车等行业的工作。

Superior that paper backing, normal flexible, the sanding belt, low abrasion, can be made into belts and special shaped products for fine sanding on furniture, wood floor, rubber, plastic, leather, metal parts, artificial board, also can be made into belts after for sanding in automotive industry.

规格 Size	性能 Performance			尺寸 Dimension				每卷重量 per roll (kg)
	厚度 Thickness	最大宽度 Max Width	最大长度 Max Length	宽度 Width	长度 Length	重量 Weight	长度 Length	
高韧性 High Tensile	1400	3000	3000	1400	3000	1400	3000	1400-3000

PKE51-1

超耐磨纸基砂带

Superior Abrasion grade that paper belt

PCE51

超耐磨纸基砂带

Superior grade that paper belt

超耐磨纸基砂带，具有适中的柔软度，砂面平整，结构细小，适合做各种砂带，砂带和砂带制品。适用范围：主要用于家具、地板、橡胶、塑料、皮革、木材、金属、人造板的打磨和抛光。

For paper backing, normal flexible, the sanding belt, low abrasion, can be made into belts and special shaped products for fine sanding on furniture, wood floor, rubber, plastic, leather, metal parts, artificial board.

规格 Size	性能 Performance			尺寸 Dimension				每卷重量 per roll (kg)
	厚度 Thickness	最大宽度 Max Width	最大长度 Max Length	宽度 Width	长度 Length	重量 Weight	长度 Length	
超耐磨 Superior	1400	3000	3000	1400	3000	1400	3000	1400-3000

AX207

铝制专用刮刀

Aluminum made scuffs and for Top Deck

刮刀为铝制专用刮刀，强度高，耐磨性好，使用寿命长。刮刀硬度好，综合性价比高。适用范围：主要用于加工玻璃尺寸刮刀片，用于各种金属和非金属表面磨擦抛光。

Aluminum made specially designed for making for glass. High grinding and high efficiency. With performance consumption of working parts and long lasting grinding. Generally used for making for glass to polish on all metal and nonmetal.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

DCY71

硬材料刮刀

Hard outside scraper working tool

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Hard fast working tool, very high strength and low abrasion, specially for making with fast for high-speed and heavy duty polishing. Generally used for polishing all kinds of glass, such as high strength fibreglass, medium density fibreglass, carbon fibre, ceramic, granite, concrete, glass, etc.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

BCY71

硬材料刮刀

Hard outside standard scuff working tool

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Hard working tool, very high strength and excellent grinding efficiency. Generally used for making with fast to push on various kinds such as medium density fibreglass, fibreglass, and decorative glass.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

GXC98

硬材料刮刀

Hard outside scuff working tool

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Right working tool, very good strength and good performance on grinding. Generally used for making with fast to push on fibreglass, fibreglass and glass, concrete, ceramic tiles, granite, rubber, plastic and furniture.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

GXK51-PL

硬材料刮刀

Hard outside scuff working tool

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Right working tool, very good strength and good performance on grinding. Generally used for making with fast to push on fibreglass, fibreglass and glass, concrete, ceramic tiles, granite, rubber, plastic and furniture.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

BCY71-L

硬材料刮刀

Hard outside scuff working tool for glass

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Fast outside scuff working, especially designed for polishing glass. Very high strength, good balance of working time, low abrasion. Generally used for making with fast for polishing and cleaning on fibreglass, fibreglass, fibreglass and all metal sheets. Good appearance after polishing and cleaning, strong grinding and long lasting angle.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

刮刀为硬材料，具有超硬的强度和最小的磨损率，特别适合于快速抛光。适用范围：用于加工各种材料，如玻璃、塑料、橡胶、金属、陶瓷、大理石、陶瓷、玻璃等。特别适合于各种材料的抛光。

Right working tool, very good strength and good performance on grinding. Generally used for making with fast to push on fibreglass, fibreglass and glass, concrete, ceramic tiles, granite, rubber, plastic and furniture.

规格 Specification			尺寸 Size				重量/重量 Weight g/oz
长度 Length	最大长度 Max length	厚度 Thickness	长度 Length	重量 Weight	长度 Length	重量 Weight	
1000mm	1400	2.0mm		■	■		750g/26.5oz

GXK51LE

普通型专用砂带

General Purpose Sand making belt

适用范围：适合一般金属和非金属的磨削和抛光，以及用于手持式砂带机的CNC应用。

Suit General steel making, suitable for making various belts. Generally used for metal and non-metal polishing, working speed of portable grinder for CNC applications.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750

GXK51-K

手持型专用砂带

Hand grip aluminum oxide making belt

产品结构好，易于掌握。适用范围：用于手工磨削或手持式工具磨削，用于碳钢、铸钢以及一般金属的打磨，也可特殊磨削小零件和铜铝件。

Good structure, easy for hand grip. Generally used for portable grinding on hardware, heat-treated metal and normal metals. Also can be made of various belts.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750

GXK61

双金属专用砂带

Aluminum oxide reinforced making belt

适用范围：适合加工金属和非金属的磨削和抛光，如铸钢、铸铝等。

Suit stainless steel making. Generally used for wet grinding or polishing with oil work on forging parts.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750

AX308

磨削型专用砂带

Grinding aluminum oxide belt roll for flap disc

磨削型专用砂带砂带，采用高硬度磨料制造，产品磨削性好，加工效率高。产品结构好，使用寿命长。适用范围：主要加工金属和非金属的打磨，用于各种金属和非金属磨削和抛光。

Grinding aluminum oxide, specially designed for making flap discs. Good grinding and high efficiency. With synchronous consumption of grinding grains and long lasting polishing, generally used for making flap discs in grinding on all metal and non-metal.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750

AX307

磨削型专用砂带

Grinding aluminum oxide belt roll for flap disc

磨削型专用砂带砂带，采用高硬度磨料制造，产品磨削性好，使用寿命长。产品结构好，使用寿命长。适用范围：主要加工金属和非金属的打磨，用于各种金属和非金属磨削和抛光。

Grinding aluminum oxide, specially designed for making flap discs. Good grinding and high efficiency. With synchronous consumption of grinding grains and long lasting polishing, generally used for making flap discs in grinding on all metal and non-metal.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750

AX208

双金属专用砂带

Aluminum oxide belt roll for flap disc

磨削型专用砂带砂带，磨料磨料，加工效率高且使用寿命长。使用寿命长。适用范围：主要用于加工金属和非金属的打磨，用于各种金属和非金属磨削和抛光。

Aluminum oxide, specially designed for making flap discs. Good grinding and high efficiency. With synchronous consumption of grinding grains and long lasting polishing, generally used for making flap discs in grinding on all metal and non-metal.

规格 Specification	基本参数 Basic Data		性能参数 Performance				备注 Remarks
	厚度 Thickness	最大宽度 Max width	最大长度 Max length	硬度 Hardness	弹性 Elongation	伸长率 Elongation	
通用型	1.00	3000	3000		■	■	750-1750



中国的玉立 世界的犀利



中国玉立集团第一工业园 Sharpness manufacturing base I



中国玉立集团第二工业园 Sharpness manufacturing base II

企业邮箱

内贸部: sales@sharpness.com.cn

外贸部: export@sharpness.com.cn

电邮部: call@sharpness.com.cn

<https://sharpness.en.alibaba.com/>

集团总部: 中国湖北省恩施州玉立大道114号 邮编: 417100

玉立集团销售图

